

## AMENDMENTS TO THE CLAIMS

1. **(Currently amended)** A method of implementing Realm Specific Internet Protocol in a network access system ~~comprising a plurality of network subdevices connected by a network~~, the method comprising the steps of:

(a) providing a network access system comprising a plurality of network subdevices in a chassis and connected by an internal network, the plurality including a first network subdevice and a second network subdevice, the second network subdevice having an interface on an external network;

(a)(b) requesting, via the internal network, by a the first network subdevice using a first protocol, a common external network address and one or more ports from a the second network subdevice to identify the first network subdevice during communications with an the external computer network;

(b)(c) receiving, via the internal network, the common external network address and an identifier of the one or more ports at the first network subdevice from the second network subdevice ;

(e)(d) updating entries in an address-to-address table maintained by the second network subdevice to reflect assignment of the common external network address and one or more ports to the first network subdevice; and

(d)(e) creating a combination network address for the first network subdevice with the identifier of the one or more ports and the common external network address, the combination network address identifying the first network subdevice for communications with the external computer network by way of the interface on the external network.

2. **(Original)** A computer readable medium having stored therein instructions for causing a central processing unit to execute the method of claim 1.

3. **(Currently amended)** The method of claim 1 further comprising:

~~(a)~~ (f) sending a request from the first network subdevice to the second network subdevice via the internal network;

~~(b)~~ (g) routing the request from the second network subdevice to the external ~~computer~~ network by way of the interface on the external network;

~~(e)~~ (h) receiving a reply at the second network subdevice on the common external network address for the network access system; and

~~(d)~~ (i) routing the reply from the second network subdevice to the first network subdevice via the internal network using the locally unique port from the combination network address.

4. **(Currently amended)** The method of claim 1 wherein the first protocol is a Realm Specific Internet Protocol comprising a Realm Specific Internet Protocol assign request message, a Realm Specific Internet Protocol assign response message, and ~~a~~ the combination network address involving a locally unique port and a common external network address.

5. **(Original)** The method of claim 1 wherein the common external network address is an Internet protocol address.

6. **(Original)** The method of claim 1 wherein the first network subdevice is a communications card.

7. **(Original)** The method of claim 6 wherein the communications card comprises a Realm Specific Internet Protocol host and an Internet protocol interface.

8. **(Original)** The method of claim 7 wherein the communications card further comprises a data application and a device control application.

9. **(Original)** The method of claim 1 wherein the second network subdevice is a router or a port server.

10. **(Original)** The method of claim 1 wherein the second network subdevice comprises a Realm Specific Internet Protocol gateway and a plurality of Internet protocol interfaces.

11. **(Currently amended)** The method of claim 1 wherein the external ~~computer~~ network is any of the Internet, an intranet or a public-switched telephone network.

12. **(Previously presented)** The method of claim 11 wherein the common external network address is an Internet protocol address.

13. **(Currently amended)** The method of claim 1 wherein the plurality of subdevices

~~on~~ of the network access system comprise a local area network and the external network is any of the Internet or an intranet.

Claims 14 – 33: **(Cancelled)**

34. **(Currently Amended)** A network access device, comprising in combination within a chassis:

- (a) ~~a first~~ an internal network;
  - (b) a first network subdevice comprising a network client on the ~~first~~ internal network; and,
  - (c) a second network subdevice on the ~~first~~ internal network comprising a network address server for allocating ~~a second~~ an external network address and one or more ports to the first network subdevice, wherein the second network subdevice has ~~a first~~ an internal network address for communicating with other network subdevices on the ~~first~~ internal network and ~~a second~~ an external network address for communicating with a plurality of network devices on ~~a second~~ an external network, and wherein the network address server is used to allocate the ~~second~~ external network address to the first network subdevice on the ~~first~~ internal network,
- wherein the first network subdevice has a first internal network address for communicating with other network subdevices on the internal network and requests from ~~a~~ the second network subdevice allocation of ~~a second~~ the external network address and one or more ports for communicating with a plurality of network devices on ~~a second~~ the external network; and

wherein the first network subdevice further comprises an IP interface and the client of the first network subdevice is a Realm Specific Internet Protocol host.

35. **(Currently Amended)** A network access device, comprising in combination within a chassis:

(a) ~~a first~~ an internal network;

(b) a first network subdevice comprising a network client on the ~~first~~ internal network; and,

(c) a second network subdevice on the ~~first~~ internal network comprising a network address server for allocating ~~a second~~ an external network address and one or more ports to the first network subdevice, wherein the second network subdevice has ~~a first~~ an internal network address for communicating with other network subdevices on the ~~first~~ internal network and ~~a second~~ an external network address for communicating with a plurality of network devices on ~~a second~~ an external network, and wherein the network address server is used to allocate the ~~second~~ external network address to the first network subdevice on the ~~first~~ internal network,

wherein the first network subdevice has a first internal network address for communicating with other network subdevices on the internal network and requests from ~~a~~ the second network subdevice allocation of ~~a second~~ the external network address and one or more ports for communicating with a plurality of network devices on ~~a second~~ the external network; and

wherein the second network subdevice further comprises an IP interface and the network address server of the second network subdevice is a Realm Specific Internet Protocol gateway.

36. **(Currently Amended)** A network access device, comprising in combination within a chassis:

(a) ~~a first~~ an internal network;

(b) a first network subdevice comprising a network client on the ~~first~~ internal network; and,

(c) a second network subdevice on the ~~first~~ internal network comprising a network address server for allocating ~~a second~~ an external network address and one or more ports to the first network subdevice, wherein the second network subdevice has ~~a first~~ an internal network address for communicating with other network subdevices on the ~~first~~ internal network and ~~a second~~ an external network address for communicating with a plurality of network devices on ~~a second~~ an external network, and wherein the network address server is used to allocate the ~~second~~ external network address to the first network subdevice on the ~~first~~ internal network,

wherein the first network subdevice has a first internal network address for communicating with other network subdevices on the internal network and requests from ~~a~~ the second network subdevice allocation of ~~a second~~ the external network address and one or more ports for communicating with a plurality of network devices on ~~a second~~ the external network; and

wherein the first network subdevice further comprises a data application and a device control application.

37. **(Previously presented)** The network access device of claim 36 wherein the network access device is an Internet telephony gateway system.

38. **(Currently amended)** The network access device of claim 36 wherein the network access device is an Internet telephony gateway system and wherein the data application provides media translation functionality and the device control application provides for remote control of the first network subdevice by a network device on the ~~second~~ external network.

39. **(Previously presented)** The network access device of claim 36 wherein the network access device is an Internet telephony gateway system and wherein the first network subdevice is a MEGACO-compliant media gateway.

40. **(Currently amended)** The network access device of claim 36 wherein the network access device is an Internet telephony gateway system and wherein the ~~second~~ external network comprises an external Internet Protocol signaling network having an Internet Protocol control device and an external Internet Protocol data network having an Internet Protocol media device.

41. **(Currently amended)** The network access device of claim 36 wherein the ~~second~~ external network comprises an external Internet Protocol signaling network having an Internet Protocol control device and an external Internet Protocol data network having an Internet Protocol media device and wherein the Internet Protocol control device on the external Internet Protocol signaling network is a MEGACO-compliant media gateway controller.